SX24 the right combination of strength, power, versatility, agility and comfort

Specifications*

MODEL		SX24
Drive		4WD
Transmission		HST
ENGINE (DIESEL)		
Model		S773
Engine gross power	(SAE hp/ (kW)) / (DIN hp/ (kW))	20,5/ (27.6) / 24 (17.9)
Number of cylinders		3
Displacement	(cc)	1005
Rated speed	(rpm)	3000
Battery	(V-A)	12 - 40
Alternator	(A)	40
Fuel tank capacity	(l)	29.5
PTO		
Rear PTO	(rpm)	540
Mid PTO	(rpm)	2185
Front PTO (Option)	(rpm)	2185
HYDRAULIC		
Position control		Standard
3-point hitch category 1		Standard
Max. lifting capacity	(kg)	705
TRAVELING SYSTEM		
Power steering		Hydraulic
Brake		Wet disk
TYRE SIZE		
Terra		(F) 18x8.50-8 (R) 26x12.00-12
Turf		(F) 18x8.50-8 (R) 26x12.00-12
Agricultural		(F) 4.00-9 (R) 7-14
TRAVELING SPEED		
Forward / Reverse	(km/h)	2 groups: 0 - 8 and 0 -17 / 0 -6 and 0 - 11
DIMENSIONS TERRA/ TURF TYRES		
Length / Width / Height	(mm)	2493 / 1175 / 2288
Wheelbase / Ground clearance	(mm)	1400 / 230
Tread setting front / rear	(mm)	940 / 870
Weight incl. ROPS	(kg)	696

*The specifications are subject to change without notice.

⚠ Important information

- Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

SHIBAURA

SHIBAURA EUROPE BV
Begonialaan 7
NL - 6851 TE Huissen
T. 0031 (0)26 3269999
F. 0031 (0)26 3269990
E. info@shibaura.com
I. www.shibaura.com

Dealer:

SUBCOMPACT TRACTOR

SX24

SHIBAURA

GREAT FEATURE TO HELP YOU GET YOUR WORK DONE

- Safety lock feature ensuring you to get the engine started only with the PTO & SPEED lever in neutral.
- Adjustable seat position (Fore-and-after, height, suspension tension).
- Ergonomically designed operator controls.
- Hand throttle lever to adjust engine rpm.
- Wet disk brakes.
- Full functional instrument panel.
- Hydraulic steering
- Hydrostatic with two groups
- 4WD

Well organized instrumentpanel, lever and pedals

Cat. 1 3-point hitch and independent PTO

Two pedalsteering



Easy accessible for maintenance

SHIBAURA GIVES YOU MAXIMUM VERSATILITY

- Mid PTO
- 1,37 or 1.50 m side discharge rotary mower (option).
- Category 1 3-point hitch.
- Double acting remove valve.
- Two-spool control valve for front-mounted implement (option).
- Electric socket for trailer.
- Frontloader.
- Cabin.
- Grasscollector.
- Sweeper.
- Snow blade.
- Spreader.

SHIBAURA COMPACT DIESEL ENGINE; THE ONE YOU CAN TRUST

Low-emission diesel engine

The Shibaura diesel engines mounted on the SX24 tractor are environmentally friendly. It meets the US EPA Interim Tier-4 which is recognized as one of the toughest emission criteria in the world at present. Besides, the engine design takes the EU-DGXI stage 3A emission regulation into account. In order to satisfy upcoming emission control regulations, Shibaura will design its diesel engine to achieve better combustion efficiency, emission and less fuel consumption.



Low noise and low vibration

The Shibaura diesel engines realizes low noise and low vibration in the whole engine revolution range. The engine has proper rigidity of the cylinder block and gear case cover, which helps reducting its mechanical and combustion noise.

Compact and light-weight

Applying Finite Element Method (FEM) for structural analysis, Shibaura designs its diesel engine to be compact and light-weight on the basis of the appropriate balance of rigidity, strength and weight.

Easy maintenance

The Shibaura diesel engines are ideal when it comes to easy maintenance. On one side of the engine, you can check the oil level, replace the oil filter and complete some other necessary maintenance.

ATTACHMENTS & ACCESSORIES

FRONTLOADER

CABIN

GRASSCOLLECTOR

SWEEPER

SNOW BLADE



SPREADER

LIFT TRIANGLE



FRONTLIFT + PTO

TYRES

FLAILMOWER

MIDMOUNTED MOWER

FRONTMOWER